



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/681,238

10/09/2003

Jason Dirk Rusmisl

ALC 3092

6559

7590 06/27/2008
KRAMER & AMADO, P.C.
1725 Duke Street, Suite 240
Alexandria, VA 22314

EXAMINER

MATTIS, JASON E

ART UNIT

PAPER NUMBER

2616

MAIL DATE

DELIVERY MODE

06/27/2008

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/681,238	Applicant(s) RUSMISEL ET AL.	
	Examiner JASON E. MATTIS	Art Unit 2616	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 04 April 2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-14 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-14 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) ☒ Notice of References Cited (PTO-892) | 4) ☐ Interview Summary (PTO-413) |
| 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) ☐ Information Disclosure Statement(s) (PTO/SB/08) | 5) ☐ Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) ☐ Other: _____ |

DETAILED ACTION

1. This Office Action is in response to the Appeal Brief filed 4/4/08. Claims 1-14 are currently pending in the application.
2. Applicant's request for reconsideration of the finality of the rejection of the last Office action is persuasive and, therefore, the finality of that action is withdrawn.

Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –
(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

4. Claims 1-3 and 9-14 are rejected under 35 U.S.C. 102(e) as being anticipated by Lau et al. (U.S. Pat. 7093160 B2).

With respect to claim 1, Lau et al. discloses in a node of a telecommunications network comprising redundant processor modules with one module being an active module and another module being an inactive module of maintaining a method of maintaining the inactive module in hot standby mode with the active module (**See the**

abstract, column 4 lines 7-31, and Figure 1 of Lau et al. for reference to a router 10, which is a node of a telecommunications network, comprising and active MPLS control card 12 and a standby MPLS control card 14, which are redundant processor modules, and for reference to a method of implementing protocol redundancy to maintain the standby card 14 in a hot-standby mode with the active card 12). Lau et al. also discloses each redundant routing processor including a primary control processor, a run time control processor, a message processor and a distributed layer processor **(See column 4 lines 7-31, column 5 lines 6-55, and Figures 1 and 2 of Lau et al. for reference to both the active and standby control cards including system architecture 100 running redundancy software 18 for implementing MPLS redundancy in a router including a control plane 102, which acts as and performs the functions of a primary control processor, a run time control processor, and a message processor, and redundancy software 18, data plane 104, and layer 2 interface 106, which together act as and perform the functions of a distributed layer processor).** Lau et al. further discloses coordinating operations of the run time control processors, the message processors, and the distributed layer processors, with the primary control processors **(See column 5 lines 6-55 and Figure 2 of Lau et al. for reference to each of the devices of the control plane 102, data plane 104, and layer 2 interface 106 being connected to and coordinated with one another through the control plane 102).** Lau et al. also discloses allocating resources between the message processors and the distributed layer processors with the run time control processors **(See column 3 lines 54-67,**

column 5 lines 26-27 and Figure 2 of Lau et al. for reference to the data plane 104 controlling allocation of resources for devices between the control plane 102 and the layer 2 interface 106). Lau et al. further discloses sending only a status affecting message affecting the status from the active module to the inactive module and updating the inactive module in response to the status affecting message **(See column 4 lines 32-54 and column 5 line 56 to column 6 line 7 of Lau et al. for reference to redundancy software 18 running in the control plane 102 sending update data including connection state data, which is status affecting data, from the active card 12 to the standby card 14 and for reference to the standby card 14 being updating in accordance with the update data to mirror the active card 12).**

With respect to claim 2, Lau et al. discloses the active module holding the connection by exchanging signaling messages **(See column 3 lines 32-48 and column 4 lines 7-15 of Lau et al. for reference to the active card 12 holding connections by exchanging MPLS signaling messages with other routers of the network).** Lau et al. also discloses the active module filtering out only the status affecting messages and sending a synchronization message to the inactive module containing information on how the status of the connection has been changed **(See column 4 lines 32-54 and column 5 line 56 to column 6 line 7 of Lau et al. for reference to filtering messages to send only status affecting messages to the standby card 14, i.e. blocking timer event messages from the standby card 14, and for reference to sending update data in a synchronization message to the standby card 14).**

With respect to claim 3, Lau et al. discloses the active module holding routing information, making decisions based on the signaling messages, and updating the routing information **(See column 3 lines 32-48 and column 4 lines 7-15 of Lau et al. for reference to the active card 12 making routing decision based on stored routing table information and for reference to the active card 12 updating the routing table)**. Lau et al. also discloses the active module sending the synchronization message to the inactive module **(See column 4 lines 32-54 and column 5 line 56 to column 6 line 7 of Lau et al. for reference to sending update data in a synchronization message to the standby card 14)**.

With respect to claim 9, Lau et al. discloses in a node of a telecommunications network comprising redundant MPLS processor modules with one module being an active module and another module being an inactive module of maintaining a method of maintaining the inactive module in hot standby mode with the active module **(See the abstract, column 4 lines 7-31, and Figure 1 of Lau et al. for reference to a router 10, which is a node of a telecommunications network, comprising and active MPLS control card 12 and a standby MPLS control card 14, which are redundant processor modules, and for reference to a method of implementing protocol redundancy to maintain the standby card 14 in a hot-standby mode with the active card 12)**. Lau et al. also discloses each redundant routing processor including a primary control processor, a run time control processor, a message processor and a distributed layer processor **(See column 4 lines 7-31, column 5 lines 6-55, and Figures 1 and 2 of Lau et al. for reference to both the active and standby control**

cards including system architecture 100 running redundancy software 18 for implementing MPLS redundancy in a router including a control plane 102, which acts as and performs the functions of a primary control processor, a run time control processor, and a message processor, and redundancy software 18, data plane 104, and layer 2 interface 106, which together act as and perform the functions of a distributed layer processor). Lau et al. further discloses coordinating operations of the run time control processors, the message processors, and the distributed layer processors, with the primary control processors **(See column 5 lines 6-55 and Figure 2 of Lau et al. for reference to each of the devices of the control plane 102, data plane 104, and layer 2 interface 106 being connected to and coordinated with one another through the control plane 102).** Lau et al. also discloses allocating resources between the message processors and the distributed layer processors with the run time control processors **(See column 3 lines 54-67, column 5 lines 26-27 and Figure 2 of Lau et al. for reference to the data plane 104 controlling allocation of resources for devices between the control plane 102 and the layer 2 interface 106).** Lau et al. further discloses sending only a status affecting message affecting the status from the active module to the inactive module and updating the inactive module in response to the status affecting message **(See column 4 lines 32-54 and column 5 line 56 to column 6 line 7 of Lau et al. for reference to sending update data including connection state data, which is status affecting data, from the active card 12 to the standby card 14 and for reference to the standby card 14 being updating in accordance with the update data to mirror the**

active card 12). Lau et al. also discloses performing an activity switch from the active module to the inactive module to reverse the roles of the modules **(See column 4 lines 32-54 of Lau et al. for reference to, upon failure of the current active card 12, switching the state of the current standby card 14 so that card 14 becomes the new active card and card 12 becomes the new standby card).**

With respect to claim 10, Lau et al. discloses the newly active module performing an audit of the label switching paths before the activity switch is performed **(See column 4 lines 32-54 for reference to the standby switch 14 receiving initial redundancy data including provision and MPLS state data, and for reference to the standby switch 14 performing an audit by updating its information using the initial redundancy data prior to switching from standby mode to active mode).**

With respect to claim 11, Lau et al. discloses a telecommunications node comprising two routing control cards which are interchangeably maintained as active and inactive at any one time **(See the abstract, column 4 lines 7-31, and Figure 1 of Lau et al. for reference to a router 10, which is a node of a telecommunications network, comprising and active MPLS control card 12 and a standby MPLS control card 14, which are redundant routing control cards, and for reference to the cards 12 and 14 being interchangeably maintained in either active or standby at any one time).** Lau et al. also discloses the cards including a distributed processor running protocols for managing a communications path **(See column 5 lines 6-55 and Figure 2 of Lau et al. for reference to the cards 12 and 14 having redundancy software 8, data plane 104, and layer 2 interface 106, which together act as a**

distributed layer processor running protocols for managing communication paths). Lau et al. further discloses the cards including a message processor sending synchronization messages to the other control card in that, while the card is in active mode, all signaling messages are processed and synchronization messages are generated when the status of the path has changed, and, while the card is in inactive mode, receiving the synchronization messages from the other card **(See column 4 lines 32-54, column 5 lines 6-55, and Figure 2 of Lau et al. for reference to the cards 12 and 14 control plane 102 running redundancy software 18, which together act as and perform the functions of a message processor, to process messages, generate update data messages, and send the update data messages to the other card when operating in active mode and for reference to the cards 12 and 14 receiving the update data messages when operating in inactive mode).** Lau et al. also discloses allocating resources between the message processors and the distributed layer processors with a run time control processor **(See column 3 lines 54-67, column 5 lines 26-27 and Figure 2 of Lau et al. for reference to the data plane 104 controlling allocation of resources for devices between the control plane 102 and the layer 2 interface 106).** Lau et al. further discloses coordinating operations of the run time control processors, the message processors, and the distributed layer processors, with a primary control processors **(See column 5 lines 6-55 and Figure 2 of Lau et al. for reference to each of the devices of the control plane 102, data plane 104, and layer 2 interface 106 being connected to and coordinated with one another through the control plane 102).**

With respect to claim 12, Lau et al. discloses that the communication path is a label switched path **(See column 3 lines 32-48 of Lau et al. for reference to using MPLS protocol having label switched paths)**. Lau et al. also discloses the cards having state machines managing the paths and the synchronization messages containing new decisions and forwarding tables **(See column 4 lines 7-15 and column 5 line 56 to column 6 line 7 of Lau et al. for reference to the cards 12 and 14 having state machines that manage paths and update data including new routing table information)**.

With respect to claim 13, Lau et al. discloses the state machines running MPLS protocol **(See column 3 lines 32-48 of Lau et al. for reference to using MPLS protocol)**. Lau et al. also discloses performing an activity switch to reverse the roles of the control cards **(See column 4 lines 32-54 of Lau et al. for reference to, upon failure of the current active card 12, switching the state of the current standby card 14 so that card 14 becomes the new active card and card 12 becomes the new standby card)**.

With respect to claim 14, Lau et al. discloses the synchronization messages including forwarding table entry information **(See column 4 lines 7-15 of Lau et al. for reference to updating routing table information)**.

Claim Rejections – 35 USC § 103

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claims 4-8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lau et al. in view of O'Brien et al. (U.S. Publication 2008/00026696 A1)

With respect to claim 4, Lau et al. does not specifically disclose that status information is affected by setup, modification, and teardown of a connection.

With respect to claim 6, Lau et al. discloses that the processor module is an MPLS processor module using RSVP messages (**See column 5 lines 26-55 and Figure 2 of Lau et al. for reference to the cards 12 and 14 being MPLS cards using RSVP messages**). Lau et al. does not specifically disclose that status information is affected by setup, modification, and teardown of a connection.

With respect to claims 4 and 6, O'Brien et al., in the field of communication, discloses a redundant routing module updating connection status information including setup, modification, and teardown information (**See page 3 paragraphs 79-80, page 15 paragraph 294 and page 16 paragraph 317 of O'Brien et al. for reference to an active routing module updating a standby routing module of connection status information including set up, tear down, and other connection modifications**).

Updating connection status information including setup, modification, and teardown information has the advantage of making sure that a standby routing module has all the information necessary to instantly take over for an active routing module upon a failure.

It would have been obvious for one of ordinary skill in the art at the time of the invention, when presented with the work of O'Brien et al., to combine updating connection status information including setup, modification, and teardown information, as suggested by O'Brien et al., with the system and method of Lau et al., with the motivation being to make sure that a standby routing module has all the information necessary to instantly take over for an active routing module upon a failure.

With respect to claim 5, Lau et al. discloses that the connection is a label switched path with the processor performing protocols for managing the label switched path **(See column 3 lines 32-48 of Lau et al. for reference to using MPLS protocol having label switched paths)**.

With respect to claim 7, Lau et al. discloses that refresh messages are filtered **(See column 5 line 56 to column 6 line 7 of Lau et al. for reference to filtering timing event messages, which are refresh messages)**.

With respect to claim 8, Lau et al. discloses the synchronization messages including forwarding table entry information **(See column 4 lines 7-15 of Lau et al. for reference to updating routing table information)**.

Response to Arguments

7. Applicant's arguments filed 4/4/08, with respect to the rejection(s) of claim(s) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of newly cited areas of Lau et al. and newly cited O'Brien et al. (U.S. Publication US 2008/0002669 A1).

Regarding Applicant's argument that the elements of Lau et al. mapped to the message processor and distributed layer processor in the previous Office Action do not disclose the claimed message processor sending a status affecting message to update a distributed processor, the Examiner agrees. Accordingly the finality of the previous Office Action has been withdrawn, as indicated above. However, the current rejections now rely on different cited sections of Lau et al. to show a teaching a message processor sending a status affecting message to update a distributed processor.

Regarding Applicant's argument that Lau et al. does not disclose sending "only a status affecting", as claimed, the Examiner respectfully disagrees. Although Applicant argues that the provisioning data sent is not status affection data, it is unclear from the Applicant's arguments why this type of data does not fall under the category of "status affecting" messages, as claimed. Data used to provision an MPLS control card affects the operation of the card. Since provisioning information is related to the status of a control card's operation, it is a type of data that affects status, as claimed. Thus, Lau et al. does disclose sending "only a status affecting" as broadly claimed.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to JASON E. MATTIS whose telephone number is (571)272-3154. The examiner can normally be reached on M-F 8AM-5:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Firmin Backer can be reached on (571)272-6703. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

JEM

/FIRMIN BACKER/
Supervisory Patent Examiner, Art Unit 2616